MOBICONT TYPE MD 800



MD 800 with electric pump





MD 800 with loading traverse

Mobile diesel supply for building site vehicles, machinery, equipment etc. International transport of hazardous liquids according to ADR/RID and the IMDG code, packing groups II and III

- sturdy, conical outer container made of 3 mm steel sheet that protects the inner container and provides 100% spill containment
- including dipstick to test for leakage
- 100 mm ground leeway
- sturdy, changeable inner made of PE
- filling/extraction lid with 2" filling coupling, vent valve, suction hose, stopcock for the pump connection, screw-in dipstick
- lockable hood with gas compression springs
- suitable for pick-up by a pallet truck, forklift or crane

Accessories

- manual or electric pumps
- level indicator
- loading traverse
- further accessories on request

UN-APPROVALS

(h) 31HA1/Y/D/BAM 14263-BAUER/3344/

	·	ind ood man outling that else		
	Volume	Dimensions	Weight in kg	
	in l	(I x w x h) in mm	paint. / galv.	
MD 800	800	1225 x 1025 x 1625	253 / 278	

Finish: RAL 2000 RAL 3000 RAL 5012 RAL 6011 RAL 7005 hot-dip galvanized

MINI-TANK TYPE MT 235



MT 235 with manual pump

	Volume in I	Dimensions (I x w x h) in mm	Can be stacked	Total permitted weight in kg	Weight in kg
MT 235	235	800 x 800 x 1250	3 high	725	220

Suitable for filling building site vehicles and machinery, equipment etc. For the international transport of hazardous liquids according to ADR/RID and the IMDG code, packing groups II and III. For the storage of flammable liquids of GHS-categories 1 - 3

- outer container has a frame and provides 100% spill containment
- inner tank (screwed to outer container) with stacking frame, dome cover and fittings
- dipstick to register any leakage
- 2" coupling for pump
- filling coupling with threaded connection
- aeration valve
- can be locked
- suitable for pick-up by a pallet truck, forklift or crane
- for indoor and outdoor use

Accessories

- manual and electric pumps
- level indicator

UN-APPROVALS 31A/Y/D/BAM 12671-BAUER/4470/

Finish: hot-dip galvanized