## **SPECIAL WASTE CONTAINERS TYPE SAP-1**





SAP 800-1 with dual code

Finish:

hot-dip galvanized

## For the international transport of solids and paste-like substances according to ADR/RID and the IMDG code, packing groups I, II and III

- IBC according to DIN standard 30741, part 1
- dual code
- construction made of 2 mm steel sheet, lid and base frame 2.5 mm steel sheet
- reinforced edging
- full-length fork sleeves
- sturdy stacking corners with crane lifting eyes
- suitable for pick-up by a pallet truck, forklift or crane
- spring-loaded lid with a seal
- 2 lid fasteners, lockable
- automatic lid lock in 270° position
- lid support in 70° position
- max. density 1.5 kg/l

## **Accessories**

- PE foil bags (50 bags/roll)
- PE inlay
- embossed company name



SAP 800-3 with 2 lid fasteners (1 lockable)

## **UN-APPROVALS**

- (h) 11A/X/D/BAM 6007-BAUER/4960/
- **4A/X/S/D/BAM 6917-BAUER**

	<b>Volume</b> in I	Dimensions (I x w x h) in mm	Can be stacked	Total permitted weight in kg	Weight in kg
SAP 450-1	450	1200 x 1000 x 835	3 high	825	155
SAP 600-1	600	1200 x 1000 x 1055	3 high	1124	164
SAP 800-1	800	1200 x 1000 x 1235	3 high	1415	175
SAP 800-3	800	1200 x 1000 x 1235	3 high	1375	175

**10-3** 800 1200 x 1000 x 1235 3 high 1375 175