

# LIFTOMAT TYPE L



L/E 1300

**Controlled emptying of steel bunghole drums, steel drums with a lid, steel rolling hoop drums, plastic L-ring drums, plastic double L-ring drums and plastic drums with a lid ranging from 110 to 220 litres**

- range of rotation up to 270°
- 2 swivel castors Ø 175 mm and 2 fixed castors Ø 200 mm made of solid rubber, both swivel castors with brake
- safe pick-up guaranteed; drum is held by the tension band at the front and spindle at the top
- with crank handle and self-braking gear box

### Types available

#### L/E

- electro-hydraulic construction fitted with maintenance-free battery 12V/88Ah and charger for 230 V mains connection

#### L/M

- hydraulic construction with manual pump

### Individual construction on request e.g.

- "ex"-zone constructions in compliance with EU directive 2014/34/EU (L/M)



L/M 1300



L/M 600



L/M 1300 "ex"-zone construction

|          | Design            | Dimensions<br>in mm (l x w x h) | Load capacity<br>in kg | Stroke height<br>in mm | Lift height<br>in mm | Emptying height<br>in mm | Range of rotation<br>in degrees | Weight<br>in kg (painted/galv.) |
|----------|-------------------|---------------------------------|------------------------|------------------------|----------------------|--------------------------|---------------------------------|---------------------------------|
| L/M 600  | hydraulic         | 1390 x 1120 x 1230              | 350                    | 18                     | 450                  | 600                      | 270                             | 156 / 168                       |
| L/M 1300 | hydraulic         | 1390 x 1120 x 1915              | 350                    | 18                     | 1100                 | 1300                     | 270                             | 192 / 210                       |
| L/E 1300 | electro-hydraulic | 1390 x 1120 x 1915              | 350                    | --                     | 1100                 | 1300                     | 270                             | 220 / 238                       |

Finish:

RAL 2000

RAL 3000

RAL 5012

RAL 6011

RAL 7005

hot-dip galvanized