

MINI-CONTAINERS WITH DROP AWAY BASE TYPE **MSB**



MSB with guiding plates

	Volume (approx.) in m ³	Dimensions (l x w x h) in mm	Load capacity in kg	Weight in kg paint. / galv.
MSB 150	0,13	600 x 800 x 625	500	65 / 70
MSB 250	0,24	800 x 1000 x 625	500	85 / 92
MSB 400	0,37	1000 x 1200 x 625	750	109 / 117

Ideal for use in limited space

- sturdy steel construction with smooth inside surface
- trap door operated by cable from the driver's seat
- trap door closes automatically when the container is set down on the ground
- can be secured to prevent slipping and unintentional trap door operation
- 100 mm ground leeway – suitable for pallet trucks
- can be stacked (3 high)

Accessories

- 2 swivel + 2 fixed polyamide castors Ø 100 mm, one swivel castor with brake
- galvanized guiding plates for trap door

	Fork sleeve (hoops) inside dimensions in mm		
	A	B	C
	min. length of forks 1100 mm		
MSB 150	175	160	65
MSB 250	380	160	65
MSB 400	550	160	65

CONTAINERS WITH DROP AWAY BASE TYPE **SB**



The economical way to collect waste or to commission solids using a minimum of space

- sturdy construction, trap door with reinforcement
- trap door closes automatically when the container is set down on the ground
- suitable for pick-up by a forklift or crane
- guiding plates for trap door
- trap door operated by cable
- can be secured to prevent slipping and unintentional trap door operation
- can be stacked (3 high)
- wheels can be fitted later

Accessories

- 2 swivel + 2 fixed polyamide castors Ø 180 mm, one swivel castor with brake
- construction height 225 mm
- galvanized lid, can be opened from both sides

Individual constructions on request



SB with castors



SB with lid



Individual construction Type SB-G

	Volume (approx.) in m ³	Dimensions (l x w x h) in mm	Load capacity in kg	Weight in kg paint. / galv.
SB 500	0,50	1035 x 1310 x 700	1000	168 / 181
SB 750	0,75	1035 x 1310 x 930	1500	192 / 207
SB 1000	1,00	1035 x 1310 x 1160	2000	215 / 231
SB 1500	1,50	1035 x 1910 x 1160	2000	281 / 302
SB 2000	2,00	1035 x 1910 x 1465	2000	320 / 344

	Fork sleeve (hoops) inside dimensions in mm		
	A	B	C
	min. length of forks 1100 mm		
SB 500-2000	630	160	65

Finish:

RAL 2000

RAL 3000

RAL 5012

RAL 6011

RAL 7005

hot-dip galvanized