

DIESEL FILLING POINTS **TYPE TAW**



TAW with a crash guard

Private filling point for diesel and biodiesel for indoor use or under cover

- sturdy steel construction
- non-slip surface that can be walked on
- must be anchored to solid ground
- thresholds on 3 sides, can be driven on

Accessories

- crash guard
- metal skirting to connect to the wall

Individual construction on request

	Dimensions in mm (l x w x h)	Retention capacity in l	Weight approx. in kg
TAW 1	4000 x 2000 x 50	166	412
TAW 2	5000 x 2550 x 50	266	631
TAW 3	6000 x 3050 x 50	390	884

DIESEL FILLING POINTS **TYPE KPS**



Private filling point for diesel and biodiesel for indoor use or under cover

- similar to TAW, but with a plug-in splash protection wall as a standard feature: galvanized steel sheet, 1000 mm high, must be assembled on site by customer

Individual construction on request

	Dimensions in mm (l x w x h)	Retention capacity in l	Weight approx. in kg
KPS 1	4000 x 2055 x 50	166	478
KPS 2	5000 x 2550 x 50	266	712
KPS 3	6000 x 3050 x 50	390	984



- every unit tested for leakage
- diesel fuel compliant with DIN EN 590 and DIN EN 14214
- flammable liquids, GHS category 3
- hazardous to aquatic environment, GHS category 2

Finish:

RAL 7036