

HAZARDOUS MATERIALS DEPOT TYPE GD-E



GD-E/IBC 2



GD-E/IBC 2

GD-E/IBC

Storage of max. 4 x 200 litre drums or 1 x 1000 litre container (IBC) or 200 l drums in combination with 60 litre drums and/or canisters and small cans

- for indoor and outdoor use
- sump tray made of 3 mm steel sheet
- galvanized grid (load capacity 1000 kg/m²)
- 100 mm ground leeway
- superstructure closed construction made of galvanized, profiled steel sheet
- natural air circulation
- hinged door, lockable
- storage of drums possible even when pumps or funnels are fitted

Types available

GD-E

- hinged roof with 2 gas compression springs, easy to open or close

GD-E/IBC

- fixed roof

Accessories

- Drum Supports FA, galvanized
- Clip-on Rotating Supports RA, galvanized
- Can Shelves GR, galvanized




GD-E 4



GD-E 2

► **Accessories** please refer to page 105



	Max. no. of 200 litre drums/1000 litre IBCs	Dimensions in mm (l x w x h)	Retention capacity in l	Weight galv. in kg
GD-E 2	2 / -	1535 x 1290 x 1730	222	230
GD-E 4	4 / -	1535 x 1590 x 1710	280	265
GD-E/IBC	- / 1	1535 x 1590 x 2470	1110	346
GD-E/IBC 2	- / 2	2835 x 1595 x 2180	1145	530

Finish:

galvanized



- every unit tested for leakage
- flammable liquids, GHS categories 1 - 3
- hazardous to aquatic environment, GHS categories 1 - 4