

HAZARDOUS MATERIALS DEPOTS TYPE GD-E



GD-E/IBC 2



GD-E/IBC 2

GD-E/IBC

Storage of max. 4 x 200 litre drums or 1 x 1000 litre container (IBC) or 200 l drums in combination with 60 litre drums and/or canisters and small cans

- for indoor and outdoor use
- sump tray made of 3 mm steel sheet
- galvanized grid (load capacity 1000 kg/m²)
- 100 mm ground leeway
- superstructure closed construction made of galvanized, profiled steel sheet
- natural air circulation
- hinged door, lockable

Types available

GD-E

- hinged roof with 2 gas compression springs, easy to open or close

GD-E/IBC

- fixed roof

Accessories (see page 116)

- Drum Supports FA, galvanized
- Clip-on Rotating Supports RA, galvanized
- Can Shelves GR, galvanized



GD-E 4



GD-E 2

Accessories (see page 116)



| | Max. no. of 200 litre drums/1000 litre IBCs | Dimensions in mm (l x w x h) | Retention capacity in l | Weight in kg |
|------------|--|---------------------------------|----------------------------|-----------------|
| GD-E 2 | 2 / - | 1535 x 1290 x 1730 | 248 | 260 |
| GD-E 4 | 4 / - | 1535 x 1590 x 1710 | 284 | 305 |
| GD-E/IBC | - / 1 | 1535 x 1590 x 2470 | 1110 | 375 |
| GD-E/IBC 2 | - / 2 | 2835 x 1595 x 2180 | 1145 | 530 |

Finish:

galvanized



- every unit tested for leakage
- flammable liquids, GHS categories 1 - 3
- hazardous to aquatic environment, GHS categories 1 - 4