

# HAZARDOUS MATERIALS DEPOTS TYPE GD



GD-C, GD-B and GD-A with GR-C



**Storage of max. 2 x 200 litre drums or a 200 l drum in combination with 60 litre drums and/or canisters and small cans**

- sump tray made of 3 mm steel sheet
- galvanized grid (load capacity 1000 kg/m<sup>2</sup>)
- 100 mm ground leeway

## Types available

### GD-A

- for indoor use
- splash protection walls
- safety chain

### GD-B

- for outdoor use
- splash protection walls
- "all weather" glass fibre reinforced plastic hood (red) with gas compression springs
- barrel lock

### GD-C

- for indoor use
- mesh walls and hood (red) to allow natural air circulation
- barrel lock

## ▶ Accessories (see page 116)



- every unit tested for leakage
- flammable liquids, GHS categories 1 - 3 (GD-A and GD-C)
- hazardous to aquatic environment, GHS categories 1 - 4



- every unit tested for leakage
- flammable liquids, flash point >55°C (GD-B)
- hazardous to aquatic environment, GHS categories 1 - 4

	Max. no. of 200 litre drums	Dimensions (l x w x h) in mm	Retention capacity in l	Weight in kg paint. / galv.
GD-A	2	1420 x 790 x 1365	254	151 / 161
GD-B	2	1460 x 830 x 1460	254	174 / 184
GD-C	2	1430 x 820 x 1390	254	149 / 159

Finish:

RAL 2000

RAL 3000

RAL 5012

RAL 6011

RAL 7005

hot-dip galvanized