

SUMP TRAYS TYPE AW



AW 450



AW 800

Storage of max. 10 x 200 litre drums or 3 x 1000 litre containers (IBCs) or 200 l drums or IBCs in combination with 60 litre drums and/or canisters and small cans

- construction made of 3 mm steel sheet
- 100 mm ground leeway
- galvanized grid (load capacity 1000 kg/m²)

Type available

Type AW/SW

- with splash protection wall on 3 sides, made of galvanized steel sheet, height 1000 mm

Accessories (see page 116)

Individual construction on request



AW 1000-2

AW 1000-10F



AW 1000

AW 1000-3/SW (with splash protection wall)

	Max. no. of 200 litre drums/1000 litre IBCs	Dimensions (l x w x h) in mm	Retention capacity in l	Weight in kg paint. / galv.
AW 450	4 / -	1460 x 1460 x 355	525	144 / 155
AW 800	4 / -	1460 x 1460 x 525	885	165 / 178
AW 1000	- / 1	1460 x 1460 x 630	1100	180 / 194
AW 1000-2	- / 2	2650 x 1300 x 435	1135	226 / 239
AW 1000-10F	10 / 2	2690 x 1650 x 375	1186	274 / 294
AW 1000-3	- / 3	3850 x 1300 x 340	1160	294 / 310



- every unit tested for leakage
- flammable liquids, GHS categories 1 - 3
- hazardous to aquatic environment, GHS categories 1 - 4